

MEGA-TILE FIXER

WATER PROOF TILE FIXING ADHESIVE

MEGA Tile Fixer is a grey powder tile fixing adhesive based on cement , sand and high performance polymers , specially formulated for higher bond strengths and water – resistant , thin or thick bed method ceramic floor and wall tile adhesive for interior / exterior installations. Its excellent adhesion properties help in fixing tiles over existing tiles .

Complies with BS 5385 : 1976 part I Appendix A .

PRIMARY USES :

- Fixing ceramic, glazed , mosaic, granite tiles to concrete , cement/ sand screed, and existing ceramics/ terrazzo tiles , etc .
- Tiles and stones cladding on exterior walls and columns .
- Fixing tiles on areas which are likely to remain wet e.g. swimming pools, bathrooms, kitchens etc .

ADVANTAGES :

- Excellent adhesion to most building materials .
- Flexible to accommodate normal floor movements .
- Can be applied on smooth surfaces .
- Highly workable – faster work .
- Non shrink and water proofing properties .
- Do not have to wet tiles before fixing

DIRECTION OF USE :

The surface to be tiled must be sound , clean , and dry .

Existing tiles should be clean and securely fixed .

It is preferable that the surface of the glazed tiles be abraded before laying tiles over them .

Add 2 parts MEGA Tile Fixer powder to 1 part potable water by volume (do not add water to the tile adhesive powder , may result in agglomeration) .

Mix thoroughly until a smooth creamy consistency is obtained .

Allow the mixture to stand for 5minutes Mix again and start applying with a notched trowel .

Apply a thin bed of 3mm thickness by notched trowel .
Lightly comb the surface and start placing tiles before the adhesive begins to surface dry .
Press tiles into the adhesive with slight twisting action to ensure good adhesion .
Tiles can be adjusted up to 10 to 15 minutes . Clean and polish the tiles with a damp sponge or cloth .

TECHNICAL DATA :

COLOR :Grey powder.
OPEN TIME :20 mins±5 mins
Pot life :Approx. 60 mins, depending on ambient temperature.
Coverage :3.5 to 4 kg per sq. m, for 3 mm thickness

PACKAGING:

5kg, 25kg

STORAGE:

Minimum shelf life of 24 months in a dry place and in sealed bags .

SAFETY PRECAUTIONS:

*Mega tile fixer powder is cementitious powder and non hazardous .
However, it should not be swallowed or allowed to come in contact with skin and eyes .*

MEGHNA RASAYAN PRIVATE LIMITED
(ISO 9001 & 14001 CERTIFIED COMPANY)

E -Mail:meghna.rasayan@gmail.com

WEBSITE: www.meghnarasayan.com